



EVO GRUBBER
Sub-soiler

*New
possibilities*

*New
release*

*New
design*



New feature:
2nd and 5th tine are
moveable backwards
for handling a larger
amount of crop
residues.

New release

EVO GRUBBER 3.0

THE AGROLUX EVO GRUBBER sub-soiler consists of a heavy-duty frame with 6 specially angled tines. The EVO Grubber has a maximum working width of 3 m and a working depth of 50 cm. The depth can be controlled by a rear crumbler type roller or double-cutter roller. The EVO Grubber distinguishes itself by lifting and loosening the soil across the full working width.

Contrary to the ordinary sub-soilers, the Agrolux EVO Grubber exploits the full working width when loosening the soil. In addition the design makes it easy to combine the sub-soiler with a power harrow, rotavator or (disc) cultivator. Which means that it is possible to work the stubble into the soil as well as subsoiling in one pass.

Mounted short on the tractor, the Agrolux EVO Grubber 3.0 is the ideal machine to combine with other implements, for multiple operations in 1 pass.





The six tines of the Agrolux EVO Grubber 3.0 are mounted in V-shape for easy releasing residues.



Technical Specifications

Working width	Transport width	Nmb. of legs	Max. working depth	Weight	Power demand
3.00 m	3.00 m	6	0.50 m	995 kg	110 - 200 hp

Accessories

- 3-point linkage for PTO implement
- Cage roller 550 mm
- Disc-cutter roller
- Shearbolt kit

Remarks

- The EVO Grubber is stone protected with shear bolt (optional)
- This makes the EVO Grubber most useful in soil with few fixed stones.

5

main arguments

- Strong frame with welded plates: small plates with extra space to release residues.
- Breaking soil in natural lines: the 6 tines lift the soil and creates an open structure of the soil to improve watermanagement and structure of the soil
- Low draft requirement: according to several tests the EVO Grubber is one of the lowest in fuel consumption combined with limited wheelslip.
- Adjustable plates at the back of the tine: easy to adjust for changing the intensity of working
- 2nd and 5th tine are moveable backwards for



Overum Industries AB
Bruksgatan 4
SE-594 72 Överum, Sweden
+46 493 361 00

agrolux-implements.com



CRAFTED WITH **CARE**, ENGINEERED TO **LAST**